



Product Number: 55135

Order Abbreviation: 35MR11/T/SP10/C(FTE) 12V

General Description: Tungsten Halogen Tru-Aim MR11 Titan Axial Filament UV-Filter Capsule Dichroic Reflector Cover Glass GU4 Bi-Pin Base 35Watt 12Volt Spot Beam (FTE)

| Product Information | |
|-----------------------------------|---------------------------------|
| Abbrev. With Packaging Info. | 35MR11TSP10CFTE 12V 10/CS 1/SKU |
| ANSI Code | FTE |
| Average Rated Life (hr) | 4000 |
| Base | GU4 Bipin |
| Beam Angle (deg) | 10 |
| Beam Type | SP |
| Bulb | MR11 |
| Centerbeam Candlepower (cp) | 6200 |
| Class | C (gas) |
| Color Rendering Index (CRI) | 100 |
| Color Temperature/CCT (K) | 3000 |
| Diameter (in) | 1.378 |
| Diameter (mm) | 35.00 |
| Ecologic | YES |
| Family Brand Name | TRU-AIM TITAN® |
| Filament | AXIAL |
| Horizontal Beam Angle (deg) | 10 |
| Lamp Finish | Covered |
| Maximum Overall Length - MOL (in) | 1.500 |
| Maximum Overall Length - MOL (mm) | 37 |
| Nominal Voltage (V) | 12.00 |
| Nominal Wattage (W) | 35.00 |
| Vertical Beam Angle (deg) | 10 |



Footnotes

- Max. seal temperature 370 C (662F)
- UV Filter capsule with axial filament in covered constant color, hard coated dichroic reflector.
- Max pin temperature 250 C.
- Max temperature at lens reflector joint 240 C.